All 5

1. A system for increasing the security and efficiency of cryptographic processing resources for postal franking machines, comprising:

- (a)\an encryption engine;
- (b) means for obtaining encrypted code in portions to be processed by the encryption engine;
- (c) random access memory;

10

15

- (d) means for placing decrypted output from the encryption engine into the random access memory.
- 2. A method for increasing the security and efficiency of cryptographic processing resources for postal franking machines, comprising:
 - (a) obtaining encrypted code in portions to be processed by an encryption engine;
 - (b) placing decrypted output from the encryption engine into random access memory.

20

3. A system for protecting cryptographic processing and memory resources for postal franking machines, comprising:

25

(a) (1) zeroizing circuitry, (2) read only memory, (3) random access memory, (4) a clock circuit, (5) non-volatile memory, (6) central cryptographic processor, (7) logic for addressing and data flow, (8)

15

20

25

crypto key retention, (9) signature algorithm execution, (10) random number generator, (11) interrupt control and porting, (12) real time calendar clocking and watch-dog timer, (13) hash algorithm, (14) secure memory management unit, and (15) host interface, all disposed within a PCMCIA Card;

- (b) means disposed within the PCMCIA Card for monitoring the amount of time a host controller is taking to complete a bus transaction;
- (c) means disposed within the PCMCIA Card for comparing the monitored amount of time to a predetermined reference time;
- (d) means disposed within the PCMCIA Card for refusing to permit completion of the bus transaction if the monitored amount of time exceeds the predetermined reference time;
- (e) an encryption engine disposed within the PCMCIA Card;
- (f) means for obtaining encrypted code in
 portions to be processed by the
 encryption engine;
- (g) random access memory disposed within the PCMCIA Card;
- (h) means for placing decrypted output from the encryption engine into the random access memory.

4. A system for protecting cryptographic processing and memory resources for postal franking machines, comprising:

5

15

20

(a) (1) zeroizing circuitry, (2) read only memory, (3) random access memory, (4) a clock circuit, (5) non-volatile memory,
(6) central cryptographic processor, (7) logic for addressing and data flow, (8) crypto key retention, (9) signature algorithm execution, (10) random number generator, (11) interrupt control and porting, (12) real time calendar clocking and watch-dog timer, (13) hash algorithm, (14) secure memory management unit, and (15) host interface, all disposed within a PCMCIA Card;

- (b) means disposed within the PCMCIA Card for monitoring the amount of time a host controller is taking to complete a bus transaction;
- (c) means disposed within the PCMCIA Card for comparing the monitored amount of time to a predetermined reference time;
- (d) means disposed within the PCMCIA Card for refusing to permit completion of the bus transaction if the monitored amount of time exceeds the predetermined reference time.
- 5. A system for protecting cryptographic
 processing and memory resources for postal franking
 machines, comprising an Application Specific Integrated

25

Circuit having (1) zeroizing circuitry, (2) read only memory, (3) random access memory, (4) a clock circuit, (5) non-volatile memory, (6) central cryptographic processor, (7) logic for addressing and data flow, (8) crypto key retention, (9) signature algorithm execution, (10) random number generator, (11) interrupt control and porting, (12) real time calendar clocking and watch-dog timer, (13) hash algorithm, (14) secure memory management unit, and (15) host interface.

6. A system for protecting cryptographic processing and memory resources for postal franking machines, comprising:

(a) an Application Specific Integrated
Circuit having (1) zeroizing circuitry,
(2) read only memory, (3) random access
memory, (4) a clock circuit, (5) nonvolatile memory, (6) central cryptographic
processor, (7) logic for addressing and
data flow, (8) crypto key retention, (9)
signature algorithm execution, (10) random
number generator, (11) interrupt control
and porting, (12) real time calendar
clocking and watch-dog timer, (13) hash
algorithm, (14) secure memory management
unit, and (15) host interface;

(b) said Application Specific Integrated
Circuit being disposed within a Personal
Computer Memory International Association
card.

7. A method for protecting cryptographic processing and memory resources for postal franking machines, comprising locating the resources to be

10

15

20

25

30

protected within an Application Specific Integrated Circuit.

8. A system for protecting cryptographic processing and memory resources for postal franking machines, comprising (1) zeroizing circuitry, (2) read only memory, (3) random access memory, (4) a clock circuit, (5) non-volatile memory, (6) central cryptographic processor, (7) logic for addressing and data flow, (8) crypto key retention, (9) signature algorithm execution, (10) random number generator, (11) interrupt control and porting, (12) real time calendar clocking and watch-dog timer, (13) hash algorithm, (14) secure memory management unit, and (15) host interface, all disposed within a PCMCIA Card.

9. A method for protecting cryptographic processing and memory resources for postal franking machines, comprising locating the resources to be protected within a PCMCIA Card.

10. A method for protecting cryptographic processing and memory resources for postal franking machines disposed within PCMCIA Card, comprising:

- (a) monitoring the amount of time a host controller is taking to complete a bus transaction;
- (b) comparing the monitored amount of time to a predetermined reference time;
- (c) refusing to permit completion of the bus transaction if the monitored amount of time exceeds the predetermined reference time.

20

15

5

10

25

machines,

processing and memory resources for postal franking

comprising:

11. A system for protecting cryptographic

15

20

25

(a) an Application Specific Integrated Circuit having (1) zeroizing circuitry, (2) read only memory, (3) random access memory, (4) a clock circuit, (5) non-volatile memory, (6) central cryptographic processor, (7) logic for addressing and data flow, (8) crypto key retention, (9) signature algorithm execution, (10) random number generator, (11) interrupt control and porting, (12) real time calendar clocking and watch-dog timer, (13) hash algorithm, (14) secure memory management

(b) an encryption engine disposed within the PCMCIA Card;

unit, and (15)\ host interface;

- (c) means for obtaining encrypted code in portions to be processed by the encryption engine;
- (d) random access memory disposed within the
 PCMCIA Card;
- (e) means for placing decrypted output from the encryption engine into the random access memory.